



EASYFIX CLAMPS

(With Nuts & Rubber Profile)



Technical Specifications • EASYFIX CLAMPS (With Nuts & Rubber Profile)

Product Code	Size (Inch)	Tighten Range D(mm)	Material	Material Dimension (bxs)	Hanging Nuts (G)	SW	Rubber	Recommended Load (kN)	Connection Screw (C)
EPCN - 01	1/4"	12-16	DIN EN 10130	1,20x20	M8	13	EPDM	0,80	M5X25
EPCN - 02	3/8"	15-19	DIN EN 10130	1,20x20	M8	13	EPDM	0,80	M5X25
EPCN - 03	1/2"	20-24	DIN EN 10130	1,20x20	M8	13	EPDM	0,80	M5X25
EPCN - 04	3/4"	26-30	DIN EN 10130	1,20x20	M8	13	EPDM	0,80	M5X25
EPCN - 05	1"	31-36	DIN EN 10130	1,20x20	M8	13	EPDM	0,80	M5X25
EPCN - 06	1 1/4"	40-43	DIN EN 10130	1,20x20	M8	13	EPDM	0,80	M5X25
EPCN - 07	1 1/2"	48-53	DIN EN 10130	1,20x20	M8	13	EPDM	0,80	M5X25
EPCN - 08	-	50-55	DIN EN 10130	1,20x20	M8	13	EPDM	0,80	M5X30
EPCN - 09	2"	60-64	DIN EN 10130	1,20x20	M8	13	EPDM	0,80	M5X30

Technical Specifications • EASYFIX CLAMPS (With Combi Nuts & Rubber Profile)

Product Code	Size (Inch)	Tighten Range D(mm)	Material	Material Dimension (bxs)	Hanging Nuts (G)	SW	Rubber	Recommended Load (kN)	Connection Screw (C)
EPCCN - 01	1/4"	12-16	DIN EN 10130	1,20x20	M8/M10	13	EPDM	0,80	M5X25
EPCCN - 02	3/8"	15-19	DIN EN 10130	1,20x20	M8/M10	13	EPDM	0,80	M5X25
EPCCN - 03	1/2"	20-24	DIN EN 10130	1,20x20	M8/M10	13	EPDM	0,80	M5X25
EPCCN - 04	3/4"	26-30	DIN EN 10130	1,20x20	M8/M10	13	EPDM	0,80	M5X25
EPCCN - 05	1"	31-36	DIN EN 10130	1,20x20	M8/M10	13	EPDM	0,80	M5X25
EPCCN - 06	1 1/4"	40-43	DIN EN 10130	1,20x20	M8/M10	13	EPDM	0,80	M5X25
EPCCN - 07	1 1/2"	48-53	DIN EN 10130	1,20x20	M8/M10	13	EPDM	0,80	M5X25
EPCCN - 08	-	50-55	DIN EN 10130	1,20x20	M8/M10	13	EPDM	0,80	M5X30
EPCCN - 09	2"	60-64	DIN EN 10130	1,20x20	M8/M10	13	EPDM	0,80	M5X30

Features and Benefits

- Quick Locking System.
- Easy installation for practitioners.
- Single Screw Clamps.
- Clamp Easy To Close With One Hand.
- Electro zinc plated (5-10 µm).
- Noise insulating lining EPDM rubber.
- Noise insulation according to DIN 4109.
- Locking screw: Flat head screw with combination recessed head.
- Fire behavior DIN4102 class B2.
- Connecting nut with combination thread M8/M10. *(With Combi Nuts & Rubber Profile)*

Rubber Profiles

- Extruded profile.
- Chlore - free
- Resistant to ozon UV, weather and sea water
- Temperature resistance from - 50C to 110C
- Shore A hardness 50±5